


SB-SOST Oilless Flanged Guide Bushing 自润滑翻边导向套



Material Specifications 材料

材料: 高力黃銅+固體潤滑劑
CuZn25Al5Mn4Fe3 + Graphite(500#SP)

How To Order 訂單方式


Code d L
● SB-SOST 09 12

Unit(單位): mm

SinoBronze Standard No.	d	L	t	D	Tolerance 公差		D1	d H7
					e7	k6		
SB-SOST-0912		12						
SB-SOST-0917		17						
SB-SOST-0922	9	22					9	
SB-SOST-0927		27						
SB-SOST-0936		36						
SB-SOST-1012		12	3	14			16	+0.015 0
SB-SOST-1017		17			-0.032 -0.050	+0.012 +0.001		
SB-SOST-1022	10	22					10	
SB-SOST-1027		27						
SB-SOST-1036		36						
SB-SOST-1217		17						
SB-SOST-1222		22						
SB-SOST-1227	12	27		18			23	12
SB-SOST-1236		36						
SB-SOST-1417		17						
SB-SOST-142		22						
SB-SOST-1427		27						
SB-SOST-1436	14	36		6			14	+0.018 0
SB-SOST-1446		46						
SB-SOST-1456		56						
SB-SOST-1517		17		20	-0.040 -0.061	+0.015 +0.002	25	
SB-SOST-1752		22						
SB-SOST-1527		27						
SB-SOST-1536	15	36					15	
SB-SOST-1546		46						
SB-SOST-1556		56						

SinoBronze Standard No.	d	L	t	D	Tolerance 公差		D1	d H7
					e7	k6		
SB-SOST-1617		17						
SB-SOST-1622		22						
SB-SOST-1627		27						
SB-SOST-1636	16	36		22			27	16
SB-SOST-1646		46						
SB-SOST-1656		56						
SB-SOST-1817		17						+0.018 0
SB-SOST-1822		22						
SB-SOST-1827		27						
SB-SOST-1836	18	36		6	-0.040 -0.061	+0.015 +0.002	18	
SB-SOST-1846		46						
SB-SOST-1856		56						
SB-SOST-1866		66						
SB-SOST-2017		17						
SB-SOST-2022		22						
SB-SOST-2027		27						
SB-SOST-2036		36						
SB-SOST-2046	20	46		26			31	+0.021 0
SB-SOST-2056		56						
SB-SOST-2066		66						

SB-SOST Oilless Flanged Guide Bushing 自润滑翻边导向套



Material Specifications 材料

材料: 高力黄铜+固体润滑剂
CuZn25Al5Mn4Fe3 + Graphite(500#SP)

How To Order 订购方式

Code d L
● SB-SOST 22 22

Unit(单位): mm

SinoBronze Standard No.	d	L	t	D	Tolerance 公差		D ₁	d H7
					e7	k6		
SB-SOST-2222	22							
SB-SOST-2227	27							
SB-SOST-2236	36							
SB-SOST-2240	22	46					22	
SB-SOST-2256	56							
SB-SOST-2266	66							
SB-SOST-2276	76							
SB-SOST-2286	86							
SB-SOST-2417	17		30	-0.040 -0.061	+0.015 +0.002	35		
SB-SOST-2422	22							
SB-SOST-2427	27							
SB-SOST-2436	36							
SB-SOST-2446	24	46				24	+0.021 0	
SB-SOST-2456	56							
SB-SOST-2466	66							
SB-SOST-2476	76							
SB-SOST-2486	86							
SB-SOST-3027	27		6					
SB-SOST-3036	36							
SB-SOST-3046	46							
SB-SOST-3056	56							
SB-SOST-3066	30	66				30		
SB-SOST-3076	76							
SB-SOST-3086	86							
SB-SOST-3096	96							
SB-SOST-30116	116		42	-0.050 -0.075	+0.018 +0.002	47		
SB-SOST-3227	27							
SB-SOST-3263	36							
SB-SOST-3246	46							
SB-SOST-3256	56							
SB-SOST-3266	32	66				32	+0.025 0	
SB-SOST-3276	76							
SB-SOST-3286	86							
SB-SOST-3296	96							
SB-SOST-32116	116							

SinoBronze Standard No.	d	L	t	D	Tolerance 公差		D ₁	d H7
					e7	k6		
SB-SOST-4056	56							
SB-SOST-4066	66							
SB-SOST-4076	76							
SB-SOST-4086	40	86					40	
SB-SOST-4096	96							
SB-SOST-40116	116							
SB-SOST-40136	136							
SB-SOST-40156	156							
SB-SOST-4256	56		54			60		
SB-SOST-4266	66							
SB-SOST-4276	76							
SB-SOST-4286	86		10			42	+0.025 0	
SB-SOST-4296	42	96		-0.060 -0.090	+0.021 +0.002			
SB-SOST-42116	116							
SB-SOST-42136	136							
SB-SOST-42156	156							
SB-SOST-6076	76							
SB-SOST-5086	86							
SB-SOST-5096	96							
SB-SOST-50116	50	116		66		72	50	
SB-SOST-50136	136							
SB-SOST-50156	156							
SB-SOST-50196	196							
SB-SOST-6096	96							
SB-SOST-60116	60	116		80		86	60	+0.030 0
SB-SOST-60136	136							
SB-SOST-60156	156							
SB-SOST-60196	196							