




Spring Bushings with Straight Slot

(Produced on Request)



d	D	D1	外径 O.D.	内径 I.D.	座孔 Housing Bore (H8)	轴 Shaft (H8)	f ₁	f ₂	L - 0.50										
14	20	20 ^{+1.5 -0.5}	20 +0.052	14 +0.11	20 +0.033	14 ^{+0.016 -0.043}	2.2	1	●	●	●	●	●						
15	20	20 ^{+1.5 -0.5}	20 +0.052	15 +0.11	20 +0.033	15 ^{+0.016 -0.043}	2.2	1	●	●	●	●	●						
16	22	22 ^{+1.5 -0.5}	22 +0.052	16 +0.11	22 +0.033	16 ^{+0.016 -0.043}	2.2	1	●	●	●	●	●						
18	24	24 ^{+1.5 -0.5}	24 +0.052	18 +0.11	24 +0.033	18 ^{+0.016 -0.043}	2.2	1	●	●	●	●	●						
20	25	25 ^{+1.5 -0.5}	25 +0.052	20 +0.13	25 +0.033	20 ^{+0.02 -0.053}	2.2	1	●	●	●	●	●						
22	28	28 ^{+1.5 -0.5}	28 +0.052	22 +0.13	28 +0.033	22 ^{+0.02 -0.053}	2.2	1	●	●	●	●	●						
24	30	30 ^{+1.5 -0.5}	30 +0.052	24 +0.13	30 +0.033	24 ^{+0.02 -0.053}	2.2	1	●	●	●	●	●						
25	32	32 ^{+1.5 -0.5}	32 +0.062	25 +0.13	32 +0.039	25 ^{+0.02 -0.053}	2.2	1	●	●	●	●	●						
28	35	35 ^{+1.5 -0.5}	35 +0.062	28 +0.13	35 +0.039	28 ^{+0.02 -0.053}	2.2	1	●	●	●	●	●						
30	38	38 ^{+1.5 -0.5}	38 +0.062	30 +0.13	38 +0.039	30 ^{+0.02 -0.053}	2.2	1	●	●	●	●	●						
32	40	40 ^{+1.5 -0.5}	40 +0.062	32 +0.16	40 +0.039	32 ^{+0.025 -0.054}	2.2	1	●	●	●	●	●						
35	44	44 ^{+2.3 -0.8}	44 +0.062	35 +0.16	44 +0.039	35 ^{+0.03 -0.054}	2.2	1	●	●	●	●	●						
36	45	45 ^{+2.3 -0.8}	45 +0.062	36 +0.16	45 +0.039	36 ^{+0.025 -0.054}	2.2	1	●	●	●	●	●						
38	48	48 ^{+2.3 -0.8}	48 +0.062	38 +0.16	48 +0.039	38 ^{+0.025 -0.054}	2.2	1	●	●	●	●	●						
40	50	50 ^{+2.3 -0.8}	50 +0.062	40 +0.16	50 +0.039	40 ^{+0.03 -0.054}	2.6	1	●	●	●	●	●						
42	52	52 ^{+2.3 -0.8}	52 +0.074	42 +0.16	52 +0.045	42 ^{+0.025 -0.054}	2.6	1	●	●	●	●	●						
45	55	55 ^{+2.3 -0.8}	55 +0.074	45 +0.16	55 +0.045	45 ^{+0.03 -0.054}	2.6	1	●	●	●	●	●						
48	58	58 ^{+2.3 -0.8}	58 +0.074	48 +0.16	58 +0.045	48 ^{+0.03 -0.054}	2.6	1	●	●	●	●	●						
50	60	60 ^{+2.3 -0.8}	60 +0.074	50 +0.16	60 +0.045	50 ^{+0.025 -0.054}	2.6	1	●	●	●	●	●						
52	60	60 ^{+2.3 -0.8}	60 +0.074	52 +0.19	60 +0.045	52 ^{+0.03 -0.076}	2.6	1	●	●	●	●	●						
55	65	65 ^{+2.3 -0.8}	65 +0.074	55 +0.19	65 +0.045	55 ^{+0.03 -0.076}	2.6	1	●	●	●	●	●						
60	70	70 ^{+2.3 -0.8}	70 +0.074	60 +0.19	70 +0.045	60 ^{+0.03 -0.076}	2.6	1	●	●	●	●	●						
65	75	75 ^{+3.0 -1.0}	75 +0.074	65 +0.19	75 +0.045	65 ^{+0.03 -0.076}	2.6	1	●	●	●	●	●						
70	80	80 ^{+3.0 -1.0}	80 +0.074	70 +0.19	80 +0.045	70 ^{+0.03 -0.076}	3.2	1	●	●	●	●	●						
75	85	85 ^{+3.0 -1.0}	85 +0.087	75 +0.19	85 +0.054	75 ^{+0.03 -0.076}	3.2	1	●	●	●	●	●						
80	90	90 ^{+3.0 -1.0}	90 +0.087	80 +0.19	90 +0.054	80 ^{+0.03 -0.076}	3.2	1	●	●	●	●	●						
85	95	95 ^{+3.0 -1.0}	95 +0.087	85 +0.22	95 +0.054	85 ^{+0.036 -0.09}	3.2	1	●	●	●	●	●						
90	100	100 ^{+3.0 -1.0}	100 +0.087	90 +0.22	100 +0.054	90 ^{+0.036 -0.09}	3.2	1	●	●	●	●	●						
95	105	105 ^{+3.0 -1.0}	105 +0.087	95 +0.22	105 +0.054	95 ^{+0.036 -0.09}	3.2	1	●	●	●	●	●						
100	115	115 ^{+3.0 -1.0}	115 +0.087	100 +0.22	115 +0.054	100 ^{+0.036 -0.09}	3.2	1	●	●	●	●	●						
105	115	115 ^{+3.0 -1.0}	115 +0.087	105 +0.22	115 +0.054	105 ^{+0.036 -0.09}	3.2	1	●	●	●	●	●						

Notes: * Standard material: hardened spring steel - AISI6150, 50CrV4 (DIN1.8159), SUP 10, 50CrVA, CK67, 65 Mn --etc.

* All sizes are in Metric " mm ".

* Speical dimenions and toleranes are made to customer' request.

* Surface treatment is optional: Zinc plating / Phosphate coating ; Tin plating.