



SB-UWP Oilless Wear Plate 自润滑板




W=18-38, L=50-100
W=48, L=75-125




W=75, L=75-125
W=100, L=100-125



W=18-48, L=150



W=75-100, L=150




Material Specifications 材料

材料: 高力青铜+固体润滑剂
CuZn25Al5Mn4Fe3 + Graphite(500#SP)

How To Order 订单方式

Code W L
● SB-UWP 18 50



Thickness = 5 mm





Unit(单位): mm

| SinoBronze Standard No. | W | L | W ₁ | L ₁ | d | h | Mounting Bolt 螺栓 |
|-------------------------|----|-----|----------------|----------------|-----|-----|------------------|
| ● SB-UWP-1850 | 18 | 50 | - | 20 | 6.5 | 1.5 | M6 |
| SB-UWP-1875 | | 75 | | 45 | | | |
| SB-UWP-18100 | | 100 | | 70 | | | |
| SB-UWP-18150 | | 150 | | 60 | | | |
| SB-UWP-2850 | 28 | 50 | - | 20 | 10 | 0.8 | M8 |
| SB-UWP-2875 | | 75 | | 45 | | | |
| SB-UWP-28100 | | 100 | | 70 | | | |
| SB-UWP-28150 | | 150 | | 60 | | | |
| SB-UWP-3850 | 38 | 50 | - | 20 | | | |
| SB-UWP-3875 | | 75 | | 45 | | | |
| SB-UWP-38100 | | 100 | | 70 | | | |
| SB-UWP-38150 | | 150 | | 60 | | | |

| SinoBronze Standard No. | W | L | W ₁ | L ₁ | d | h | Mounting Bolt 螺栓 |
|-------------------------|-----|-----|----------------|----------------|----|-----|------------------|
| SB-UWP-4875 | 48 | 75 | - | 45 | | | |
| SB-UWP-48100 | | 100 | | 70 | | | |
| SB-UWP-48125 | | 125 | | 95 | | | |
| SB-UWP-48150 | | 150 | | 60 | | | |
| SB-UWP-7575 | 75 | 75 | 45 | 45 | 10 | 0.8 | M8 |
| SB-UWP-75100 | | 100 | | 70 | | | |
| SB-UWP-75125 | | 125 | | 95 | | | |
| SB-UWP-75150 | | 150 | | 60 | | | |
| SB-UWP-100100 | 100 | 100 | | 70 | | | |
| SB-UWP-100125 | | 125 | | 95 | | | |
| SB-UWP-100150 | | 150 | | 60 | | | |

SB-SOLP Oilless Wear Plate 自润滑板



Material Specifications 材料

材料: 高力黄铜+固体润滑剂
CuZn25Al5Mn4Fe3 + Graphite(500#SP)

How To Order 订货方式

Code W L
● SB-SOLP 35 100

Unit(单位): mm

| SinoBronze Standard No. | W | L | Bolt Position 螺栓位置 | | Bolt Qty 螺栓数量 |
|-------------------------|----|-----|--------------------|----|---------------|
| | | | L1 | L2 | |
| ● SB-SOLP-35100 | 35 | 100 | 60 | - | 2 |
| SB-SOLP-35150 | | 150 | 55 | - | 3 |
| SB-SOLP-35200 | | 200 | 55 | 50 | 4 |
| SB-SOLP-35250 | | 250 | 70 | 70 | |
| SB-SOLP-35300 | | 300 | 65 | 65 | 5 |
| SB-SOLP-35350 | | 350 | 80 | 75 | |
| SB-SOLP-50100 | 50 | 100 | 60 | - | 2 |
| SB-SOLP-50150 | | 150 | 55 | - | 3 |
| SB-SOLP-50200 | | 200 | 55 | 50 | 4 |

| SinoBronze Standard No. | W | L | Bolt Position 螺栓位置 | | Bolt Qty 螺栓数量 |
|-------------------------|----|-----|--------------------|-----|---------------|
| | | | L1 | L2 | |
| SB-SOLP-50250 | 50 | 250 | 70 | 70 | 4 |
| SB-SOLP-50300 | | 300 | 65 | 65 | |
| SB-SOLP-50350 | | 350 | 80 | 75 | 5 |
| SB-SOLP-75150 | 75 | 150 | 110 | - | 4 |
| SB-SOLP-75200 | | 200 | 80 | - | 6 |
| SB-SOLP-75250 | | 250 | 105 | - | |
| SB-SOLP-75300 | | 300 | 85 | 90 | 8 |
| SB-SOLP-75400 | | 400 | 120 | 120 | |
| SB-SOLP-75500 | | 500 | 115 | - | |