


SPFG / SOBB Oilless Flanged Bushings 自润滑翻边轴套



Material Specifications 材料

材料: 高力黄铜+固体润滑剂
CuZn25Al5Mn4Fe3 + Graphite(S00#SP)

Housing Tolerance 相配座孔公差

相配座孔公差等级推荐H7
Housing tolerance recommended H7

How To Order 订货方式

- Code d D L
 ● SPFG 06 10 10
 ● SOBB 06 10 10

I.D. φd 内径 E7	O.D. φD 外径 r6	Flange 翻边		L ^{-0.1} L _{-0.3}												
		φF	t	10	11	12	13	15	18	20	23	25				
6	10	+0.032 +0.020	+0.028 +0.019	20		●	●	●								
8	12	+0.040 +0.025		25			●		●							
10	14	+0.034 +0.023		30	3			●								
12	18			35			●			●						
13	19			40				●					●			
15	21	+0.050 +0.032	+0.041 +0.028	45				●								
16	22			50	0 -0.03				●							
18	24			55						●						
20	28			65									●			●
25	33	+0.061 +0.040		70										●		●
30	38		+0.050 +0.034	75	5											●
35	44			80												●
40	50	+0.075 +0.050		90	7											
50	62	+0.060 +0.041		110	8											
60	74	+0.062 +0.043		120												
70	85	+0.090 +0.060	+0.073 +0.051	140	10											

SPFG / SOBB Oilless Flanged Bushings 自润滑翻边轴套



Mating Shaft
相配轴

d8: High load 高负荷
e7: Light load 轻负荷
f7: High precision 高精度



Material Specifications 材料

材料: 高力青铜+固体润滑剂
CuZn25Al5Mn4Fe3+Graphite(500#SP)

Housing Tolerance 相配轴孔公差

相配轴孔公差等级推荐H7
Housing tolerance recommended H7

How To Order 订单方式

Code d D L
 ● SPFG 30 38 35
 ● SOBB 30 38 35

Unit(单位): mm

L											I.D. After Press-Fitting 压装后内孔		I.D. ϕ d 内径	
-0.1 -0.3														
27	35	37	38	47	48	50	58	60	68	80	90			
												+0.016 +0.004		6
												+0.021 +0.006		8
												+0.031 +0.013		10
														12
														13
												+0.026 +0.008		15
														16
														18
												+0.037 +0.016		20
												+0.032 +0.011		25
														30
												+0.046 +0.021		35
														40
												+0.040 +0.015		50
												+0.053 +0.023		60
														70
												+0.046 +0.016		80

※压入后内孔公差值仅供参考。
The ID tolerance after fitting is for reference.